

PRODUCT DATA SHEET

Sika® Glass Mesh

Glass Fabric for Acrylic Elastic Waterproof

DESCRIPTION

Sika® Glass Mesh is a woven glass membrane which is used to enhance Sika® Roofseal, Acrylic Elastic, waterproof membrane crack bridging performance.

USES

The use of Sika® Glass Mesh is particularly recommended where Sika® Roofseal is applied for roofs and when Sika® Roofseal is overlapping construction joints, cracks and corner fillets.

CHARACTERISTICS / ADVANTAGES

Enhance Sika® Roofseal, Acrylic Elastic, waterproof membrane crack bridging performance.

PRODUCT INFORMATION

Construction	Warp	ECG 150 1/0 (33.75 Tex)
	Fill	ECG 75 1/0 (68 Tex)
Fibre Type	Leno KN 109-AC	
Packaging	100 m/roll	
Shelf life	The product does not expire if properly stored.	
Storage conditions	Store in dry conditions at temperatures between +5°C and +30°C.	
Density	Warp	(2) 9 ± 0.5 Per inch
	Fill	9 ± 0.5 Per inch
Dimensions	Width 1140 mm.	
Thickness	0.1 ± 0.02 mm.	

TECHNICAL INFORMATION

Tensile Strength	Warp	20 Kg/Inch (Min.)
	Fill	30 Kg/Inch (Min)

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets before using any products. For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.