

PRODUCT DATA SHEET

Sika® Reemat Premium

GLASS FIBRE REINFORCEMENT MAT

DESCRIPTION

Sika® Reemat Premium is a glass fibre reinforcement mat for use with Sika® Liquid Applied Membrane systems

USES

- Reinforcement for Sikalastic® and SikaRoof® MTC Systems
- Reinforcement for SikaRoof® MTC Detailing
- Reinforcement for other Sika liquid-applied membranes (LAM)
- Suitable for waterproofing applications with complex geometry and detailing.

FEATURES

- Easy and quick application
- Easy to adjust to complicated details
- Ensures the correct thickness of the base coat
- Improves crack-bridging properties of the system
- Improves mechanical properties of the system

PRODUCT INFORMATION

Composition	Random glass fibre strand matting	
Packaging	Roll sizes:	
	Length	50m
	Width	1.0m
	Size	50sqm
	Refer to current price list for packaging variations.	
Shelf life	5 years from date of production	
Storage conditions	Product must be stored in original unopened and undamaged packaging in dry conditions and temperatures between +5 °C and +35 °C. Always refer to packaging.	
Density	120 g/m2	

SYSTEM INFORMATION

System structure	For detailed information regarding system build-ups, refer to the System or Product Data Sheet of the relevant Liquid Applied Membrane
------------------	--

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

Refer to the Sika Method Statement of the relevant Liquid Applied Membrane system

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The surface must be sound, of sufficient strength, clean, dry and free of dirt, oil, grease and other contamination. Depending on the material the substrate must be primed or mechanically cleaned. Grinding may be necessary to level the surface. Suitable substrates are such as: concrete, bituminous felts and coatings, metal, brickwork, asbestos cement, ceramic tiles, wooden substrates.

For detailed information regarding substrate preparation and primer chart please refer to the Method Statement of the corresponding Liquid Applied Membrane system.

APPLICATION

Prior the application of the Sika Liquid Applied Membrane the priming coat if used must have cured tack-free. For the Waiting Time / Overcoating please refer to the PDS of the appropriate primer. Damageable areas (handrails etc.) have to be protected with tape or plastic wrapping.

Sika® Reemat Premium is applied in combination with Sika Liquid Applied Membrane systems.

1. Apply first coat of Sika Liquid Applied Membrane with a consumption rate according to the PDS of the Sika Liquid Applied Membrane. Work only so far in advance that the material stays liquid.
2. Roll in the Sika® Reemat Premium and ensure that there are no bubbles or creases. Overlapping of Sika® Reemat Premium must be minimum 5 cm and ensure overlaps are sufficiently wet to bond.

- The roller may require only a little extra material to remain wet but no further significant material needs to be added at this stage.
- After the coat is dry enough to walk on, seal the roof area with second coat of Sika Liquid Applied Membrane with a consumption rate according to the PDS of the Sika Liquid Applied Membrane.

Please note, always begin with details prior starting with waterproofing the horizontal surface.

For detailed application information please refer to the Method Statement of the corresponding Sika Liquid Applied Membrane system.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users can always refer to the most recent version of the local Product Data Sheet for the relevant product, available on our website. The information in any downloaded version is valid as of the time of download.

SikaReematPremium-en-KH-(01-2026)-4-1.pdf

PRODUCT DATA SHEET

Sika® Reemat Premium

January 2026, Version 04.01

020915952000000004