

PRODUCT DATA SHEET

SikaWall®-720 E

Internal Repair Skim Coat

DESCRIPTION

SikaWall® 720 E is a premium grade, polymer based internal skim coat that is available in paste form.

USES

SikaWall® 720 E is applicable to repair the decoration of the wall. Such as the wall potholes, small cracks, holes, peeling, nail holes, graffiti decoration.

FEATURES

- Ready to use
- Quick drying with high bond
- Spotlessly white and smooth

PRODUCT INFORMATION

Packaging	250g/piece
Shelf life	12 months
Storage conditions	+5°C~+25°C
pH-Value	11

TECHNICAL INFORMATION

Tensile adhesion strength	0.4Mpa
Flexural toughness	100mm Round bar

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

The working temperature is 5-30°C
The coating thickness should not exceed 0.5-1mm. (1 coat)

ECOLOGY, HEALTH AND SAFETY

Must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

Remove all dust, oil or traces of foreign materials.

APPLICATION METHOD / TOOLS

1. Clean the cracks before applying, then fill with SikaWall® 720 E ;
2. Apply thin skin coat over the joint to prevent the edge from wrinkling;
3. Allow to dry before application of second coat;
4. Apply finishing coat with trowel, use sand paper and hand sander to obtain a smooth surface.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika (Cambodia) Ltd.

Legacy Business Center, Building #29
street 245
Sangkat Tuol Tom Pong 2, Khan
Chamkarmorn
12308, Phnom Penh, Cambodia
Tel: +855 23 901 450

PRODUCT DATA SHEET

SikaWall®-720 E
July 2025, Version 01.01
021840303000000045

SikaWall-720E-en-KH-(07-2025)-1-1.pdf